

Mudgee Runway and Taxiway specifications

- The strength rating of the runway(s) pavement is recorded in the table below:

ACN – PCN strength rating	Runway 04/22	Runway 16/34
PCN value	10	unrated
Pavement type	F	
Pavement subgrade	C	
MAX Take-off weight	15,650 kg	
MAX tyre pressure value	1.3 MPa	
Tyre pressure category	X-medium	
PCN evaluation method	T	

- The aerodrome reference code (ARC) number, letter and OMGWS for each runway are recorded in the table below:

Runway	ARC number	ARC letter	OMGWS
04/22	3	C	4.5m up to but not including 6 m
16/34	2	A	<4.5m

3. Each taxiway designation, code letter, width, and surface type are recorded in the table below:

Taxiway name	Taxiway designation	ARC letter	Taxiway width (m)	Taxiway surface type
Taxiway Alpha	A	C	15 m	Bitumen seal
Taxiway Bravo	B	B	13m	Bitumen seal
Taxiway Charlie	C	A	13m	Grass
Taxiway Delta	D	B	15m	Bitumen seal
Taxiway Echo	E	C	15m	Bitumen seal
Taxiway Foxtrot	F	B	12m	Bitumen seal

4. The aerodrome reference code (ARC) letter and OMGWS for each taxiway and taxilane is recorded in the table below:

Taxiway / Taxilane	ARC letter	OMGWS
TWY A	C	4.5m up to but not including 6m
TWY B	B	4.5m up to but not including 6m
TWY C	A	<4.5m
TWY D	B	4.5m up to but not including 6m
TWY E	C	4.5m up to but not including 6m
TWY F	B	4.5m up to but not including 6m

ERSA - https://www.airservicesaustralia.com/aip/current/ersa/FAC_YMDG_24MAR2022.pdf