# **BASIX**<sup>°</sup>Certificate

Building Sustainability Index www.basix.nsw.gov.au

### Single Dwelling

Certificate number: 1233743S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary Date of issue: Sunday, 22 August 2021 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary				
Project name	1221 HOUSE D			
Street address	22 Lawson Street Mudgee 2850			
Local Government Area	Mid-Western Regional Council			
Plan type and plan number	deposited 231976			
Lot no.	1			
Section no.	-			
Project type	separate dwelling house			
No. of bedrooms	4			
Project score				
Water	V 33 Target 30			
Thermal Comfort	V Pass Target Pass			
Energy	V 46 Target 40			

Certificate Prepared by	
Name / Company Name: On Point Building Design	
ABN (if applicable): 54902270203	

## **Description of project**

#### Project address

1221 HOUSE D
22 Lawson Street Mudgee 2850
Mid-Western Regional Council
Deposited Plan 231976
1
-
separate dwelling house
4
713
365
177.0
23.0
174

Assessor details and thermal lo	bads
Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m².year)	n/a
Area adjusted heating load (MJ/m <sup>2</sup> .year)	n/a
Ceiling fan in at least one bedroom	n/a
Ceiling fan in at least one living room or other conditioned area	n/a
Project score	
Water	✓ 33 Target 30
Thermal Comfort	V Pass Target Pass
Energy	V 46 Target 40

#### Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		<b>~</b>	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		<b>~</b>	~
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		<b>~</b>	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 4000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	<ul> <li>Image: A set of the set of the</li></ul>	~
The applicant must configure the rainwater tank to collect rain runoff from at least 365 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		<b>~</b>	~
The applicant must connect the rainwater tank to:			
<ul> <li>at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.)</li> </ul>		<ul> <li>Image: A second s</li></ul>	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	<b>~</b>	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	<b>v</b>	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - framed (weatherboard, fibre cement, metal clad)	2.20 (or 2.60 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4 (up), roof: foil/sarking	unventilated; dark (solar absorptance > 0.70)
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 4 (up), roof: foil/sarking	framed; dark (solar absorptance > 0.70)

 Note
 • Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

 Note
 • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check	
Windows, glazed doors and skylights				
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~	
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~	
The following requirements must also be satisfied in relation to each window and glazed door:	<b>~</b>	<b>v</b>	~	
• For the following glass and frame types, the certifier check can be performed by visual inspection.			~	
- Aluminium single clear				
- Aluminium double (air) clear				
- Timber/uPVC/fibreglass single clear				
- Timber/uPVC/fibreglass double (air) clear				

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W39	1800	1800	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
W40	600	1200	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
W41	2100	800	aluminium, single, clear	eave 4450 mm, 880 mm above head of window or glazed door	not overshadowed
W42	2100	4800	aluminium, single, clear	eave 4450 mm, 1800 mm above head of window or glazed door	not overshadowed
W43	2100	800	aluminium, single, clear	eave 4450 mm, 880 mm above head of window or glazed door	not overshadowed
W44	850	4800	aluminium, single, clear	eave 4450 mm, 340 mm above head of window or glazed door	not overshadowed
W45	1800	2800	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W46	600	1500	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
South facing	,				
W47	1800	2400	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
W48	1800	900	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
W49	1800	1800	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
W50	1800	1800	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
West facing			·		·
W51	2100	800	aluminium, single, clear	eave 150 mm, 500 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	~	<b>v</b>	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 4.5 Star (old label)		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 4.5 Star (old label)		<b>v</b>	>
The cooling system must provide for day/night zoning between living areas and bedrooms.		<b>v</b>	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 4.5 Star (old label)		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 4.5 Star (old label)		~	~
The heating system must provide for day/night zoning between living areas and bedrooms.		<b>~</b>	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		<ul> <li></li> </ul>	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		<ul> <li>Image: A set of the set of the</li></ul>	<ul> <li>✓</li> </ul>
Laundry: natural ventilation only, or no laundry; Operation control: n/a		<b>~</b>	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
<ul> <li>at least 4 of the bedrooms / study; dedicated</li> </ul>		<b>~</b>	-

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
at least 2 of the living / dining rooms; dedicated		~	~
the kitchen; dedicated		~	~
all bathrooms/toilets; dedicated		~	~
the laundry; dedicated		<b>~</b>	-
all hallways; dedicated		~	~
Natural lighting			
he applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
he applicant must install a window and/or skylight in 3 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Other			
he applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		J	

#### Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.