page 1/6

BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Alterations and Additions

Certificate number: A476053

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Alterations and Additions Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretarv

Date of issue: Tuesday, 04, October 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project address	
Project name	1317
Street address	1199 ULAN Road BUDGEE BUDGEE 2850
Local Government Area	Mid-Western Regional Council
Plan type and number	Deposited Plan 702343
Lot number	121
Section number	
Section number Project type	
	Separate dwelling house

Certificate Prepared by (please complete before submitting to Council or PCA)

Name / Company Name: On Point Building Design

ABN (if applicable): 54902270203

Fixtures and systems	Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Hot water			
The applicant must install the following hot water system in the development: gas instantaneous.	\checkmark	\checkmark	~
Lighting			
The applicant must ensure a minimum of 40% of new or altered light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting-diode (LED) lamps.		~	~
Fixtures		1	
The applicant must ensure new or altered showerheads have a flow rate no greater than 9 litres per minute or a 3 star water rating.		\checkmark	~
The applicant must ensure new or altered toilets have a flow rate no greater than 4 litres per average flush or a minimum 3 star water rating.		\checkmark	\checkmark
The applicant must ensure new or altered taps have a flow rate no greater than 9 litres per minute or minimum 3 star water rating.		\checkmark	

Construction			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Insulation requirements					
The applicant must construct the new or altered the table below, except that a) additional insula is not required for parts of altered construction	<i>✓</i>	~	~		
Construction	Additional insulation required (R-value)	Other specifications			
concrete slab on ground floor.	nil				
external wall: framed (weatherboard, fibro, metal clad)	R1.30 (or R1.70 including construction)				
flat ceiling, pitched roof	ceiling: R3.00 (up), roof: foil/sarking	medium (solar absorptance 0.475 - 0.70)			

	equirements						Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Windows a	and glazed do	ors							
					nading devices, in accordance with r each window and glazed door.	the specifications listed in the table below.	\checkmark	\checkmark	~
The following requirements must also be satisfied in relation to each window and glazed door:							\checkmark	\checkmark	
have a U-va must be cale	alue and a Solar I Iculated in accord	Heat Gair dance with	n Coefficie National	ent (SHGC) r Fenestratio	no greater than that listed in the tabl	ar glazing, or toned/air gap/clear glazing must le below. Total system U-values and SHGCs s. The description is provided for information		~	~
					f each eave, pergola, verandah, bal than 2400 mm above the sill.	cony or awning must be no more than 500 mm	\checkmark	~	\checkmark
Pergolas wit	ith polycarbonate	roof or si	milar tran	slucent mate	erial must have a shading coefficien	t of less than 0.35.		✓	\checkmark
Pergolas wit shades a pe	ith fixed battens r erpendicular winc	must have dow. The s	battens spacing b	parallel to the etween batte	e window or glazed door above which ons must not be more than 50 mm.	t of less than 0.35. ch they are situated, unless the pergola also	_	~	~
Pergolas wit shades a pe	ith fixed battens r erpendicular wind and glazed c	must have dow. The s doors gl	battens p spacing b	parallel to the etween batte equiremen	e window or glazed door above whic ens must not be more than 50 mm. nts	ch they are situated, unless the pergola also	-	~	✓ ✓
Pergolas wit shades a pe	ith fixed battens r erpendicular winc	must have dow. The s doors gl	battens spacing b	parallel to the etween batte equiremen	e window or glazed door above which ons must not be more than 50 mm.			~	~
Pergolas wit shades a pe Windows Window / do	ith fixed battens r erpendicular wind and glazed c	must have dow. The s doors gl Area of glass inc. frame	battens p spacing b azing r Oversha Height	barallel to the etween batte equiremen dowing Distance	e window or glazed door above whic ens must not be more than 50 mm. nts	ch they are situated, unless the pergola also	_	~	
Pergolas wir shades a pe Windows Window / de no.	ith fixed battens r erpendicular wind and glazed o loor Orientation	must have dow. The s doors gl Area of glass inc. frame (m2)	battens p spacing b azing r Oversha Height (m)	equiremen adowing Distance (m)	e window or glazed door above white ens must not be more than 50 mm. nts Shading device	ch they are situated, unless the pergola also Frame and glass type improved aluminium, single clear, (U-value:			~
Pergolas wit shades a pe Window / de no. W1	ith fixed battens r erpendicular wind and glazed of loor Orientation	must have dow. The s doors gl Area of glass inc. frame (m2) 2.7	battens p spacing b azing r Oversha Height (m) 0	etween batte	e window or glazed door above white ens must not be more than 50 mm. nts Shading device awning (fixed) >=900 mm eave/verandah/pergola/balcony	ch they are situated, unless the pergola also Frame and glass type improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, single clear, (U-value:			
Pergolas wit shades a pe Windows Window / do no. W1 W2	ith fixed battens r erpendicular wind and glazed of loor Orientation E E	must have dow. The s doors gl Area of glass inc. frame (m2) 2.7 1.62	e battens p spacing b lazing r Oversha Height (m) 0	equirement equirement dowing Distance (m) 0	e window or glazed door above white ens must not be more than 50 mm. nts Shading device awning (fixed) >=900 mm eave/verandah/pergola/balcony >=900 mm eave/verandah/pergola/balcony	ch they are situated, unless the pergola also Frame and glass type improved aluminium, single clear, (U-value: 6.44, SHGC: 0.75) improved aluminium, single clear, (U-value:			

Glazing require	ments			Show on DA Plans	Show on CC/CDC Plans & specs	Certifier Check
Skylights				l		
The applicant must install the skylights in accordance with the specifications listed in the table below.				\checkmark	\checkmark	\checkmark
The following requ	irements must also	be satisfied in relation to each	skylight:		\checkmark	\checkmark
Each skylight may the table below.	either match the de	escription, or, have a U-value a	and a Solar Heat Gain Coefficient (SHGC) no greater than that listed in		\checkmark	\checkmark
Skylights glaz	ing requiremen	nts				
Skylight number	Area of glazing inc. frame (m2)	Shading device	Frame and glass type			
S1	0.84	no shading	timber, double clear/air fill, (or U-value: 4.3, SHGC: 0.5)]		

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a " / " in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a "
"
"
in the "Show on CC/CDC plans & specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a " / " in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate for the development may be issued.