BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1347650S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Monday, 31 October 2022 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary				
Project name	3755 - Dollisson Secondary Dwelling			
Street address	42 Guntawang Street Gulgong 2852			
Local Government Area	Mid-Western Regional Council			
Plan type and plan number	deposited 755434			
Lot no.	240			
Section no.	-			
Project type	separate dwelling house			
No. of bedrooms	2			
Project score				
Water	V 31 Target 30			
Thermal Comfort	V Pass Target Pass			
Energy	V 45 Target 45			

Certificate Prepared by
Name / Company Name: Rohrs Refrigeration

ABN (if applicable): 37 101 256 320

Description of project

Project address

Project name	3755 - Dollisson Secondary Dwelling
Street address	42 Guntawang Street Gulgong 2852
Local Government Area	Mid-Western Regional Council
Plan type and plan number	Deposited Plan 755434
Lot no.	240
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	2
Site details	
Site area (m²)	500
Roof area (m ²)	157
Conditioned floor area (m2)	77.0
Unconditioned floor area (m2)	7.0
Total area of garden and lawn (m2)	100

Assessor details and thermal loads Assessor number n/a Certificate number n/a n/a Climate zone Area adjusted cooling load (MJ/m².year) n/a Area adjusted heating load (MJ/m².year) n/a Ceiling fan in at least one bedroom n/a Ceiling fan in at least one living room or n/a other conditioned area **Project score** Water 9 31 Target 30 Thermal Comfort Target Pass V Pass Energy 45 Target 45

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures	·		
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		~	
Alternative water	1		
Rainwater tank			
The applicant must install a rainwater tank of at least 3000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 157 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		✓	~
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		✓	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	v	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	2.06 (or 2.60 including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3.25 (up), roof: foil/sarking	unventilated; light (solar absorptance < 0.475)
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 3.26 (up), roof: foil/sarking	framed; light (solar absorptance < 0.475)

Note
 Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
 Note
 In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	 Image: A set of the set of the	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	 Image: A set of the set of the	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~
• For the following glass and frame types, the certifier check can be performed by visual inspection.			v
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
Bed 2	1200	1800	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
East facing					
Ens	900	600	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Bed 1	1500	2100	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Living	1800	1800	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Living	2100	2700	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Living	1800	1800	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed

	1				
Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
WC	900	600	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Bath	900	900	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
West facing					
Bed 1	1500	2100	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Meals	1200	1800	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed
Laundry	900	600	aluminium, single, clear	eave 450 mm, 0 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5.5 star (cold zone)		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5.5 star (cold zone)		~	~
The cooling system must provide for day/night zoning between living areas and bedrooms.		v	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 5.5 star (cold zone)		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 5.5 star (cold zone)		~	~
The heating system must provide for day/night zoning between living areas and bedrooms.		~	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		 Image: A second s	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A set of the set of the	v
Laundry: natural ventilation only, or no laundry; Operation control: n/a		~	-
Artificial lighting	·	·	
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
the laundry;			

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
• all hallways;		✓	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Other			
The applicant must install a gas cooktop & gas oven in the kitchen of the dwelling.		 Image: A set of the set of the	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.