BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1371234S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary Date of issue: Thursday, 23 March 2023 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary					
Project name	Grant Residence				
Street address	25 Grevillea Grove Rylstone 2849				
Local Government Area	Mid-Western Regional Council				
Plan type and plan number	deposited 103011				
Lot no.	24				
Section no.	-				
Project type	separate dwelling house				
No. of bedrooms	4				
Project score					
Water	V 64 Target 40				
Thermal Comfort	V Pass Target Pass				
Energy	✓ 100 Target 40				

Certificate Prepared by

Name / Company Name: SUNRAI DESIGNS

ABN (if applicable): 92439450078

Description of project

Project address

Project name	Grant Residence
Street address	25 Grevillea Grove Rylstone 2849
Local Government Area	Mid-Western Regional Council
Plan type and plan number	Deposited Plan 103011
Lot no.	24
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	4
Site details	
Site area (m²)	23330
Roof area (m ²)	351
Conditioned floor area (m2)	210.5
Unconditioned floor area (m2)	21.9
Total area of garden and lawn (m2)	1000

Assessor details and thermal loads							
Assessor number	n/a						
Certificate number	n/a						
Climate zone	n/a						
Area adjusted cooling load (MJ/m ² .year)	n/a						
Area adjusted heating load (MJ/m ² .year)	n/a						
Ceiling fan in at least one bedroom	n/a						
Ceiling fan in at least one living room or other conditioned area	n/a						
Project score							
Water	64	Target 40					
Thermal Comfort	V Pass	Target Pass					
Energy	v 100	Target 40					

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Landscape			
The applicant must plant indigenous or low water use species of vegetation throughout 50 square metres of the site.	~	~	
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 6 but <= 7.5 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 36000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 351 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		~	~
 the cold water tap that supplies each clothes washer in the development 		~	~
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	~
all hot water systems in the development		v	-

page 3/11

ater Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all indoor cold water taps (not including taps that supply clothes washers) in the development		~	~

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	v	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	2.06 (or 2.60 including construction)	
external wall - framed (weatherboard, fibre cement, metal clad)	2.20 (or 2.60 including construction)	
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 4 (up), roof: foil backed blanket (55 mm)	framed; dark (solar absorptance > 0.70)
ceiling and roof - flat ceiling / flat roof, framed	ceiling: 4 (up), roof: foil backed blanket (55 mm)	framed; dark (solar absorptance > 0.70)

Note • Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~
• For the following glass and frame types, the certifier check can be performed by visual inspection.			~
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
D06	2100	2400	aluminium, double (air), clear	eave 600 mm, 600 mm above head of window or glazed door	not overshadowed
D07	2100	2400	aluminium, double (air), clear	eave 600 mm, 600 mm above head of window or glazed door	not overshadowed
D08	2100	3600	aluminium, double (air), clear	eave 450 mm, 600 mm above head of window or glazed door	not overshadowed
D02	2100	2400	aluminium, double (air), clear	eave 450 mm, 600 mm above head of window or glazed door	not overshadowed
W01	600	1800	aluminium, double (air), clear	eave 450 mm, 600 mm above head of window or glazed door	not overshadowed
W02	600	1800	aluminium, double (air), clear	eave 450 mm, 600 mm above head of window or glazed door	not overshadowed
W12	800	1700	aluminium, double (air), clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed

					<u> </u>
Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W13	800	3400	aluminium, double (air), clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W15A	1100	6000	aluminium, double (air), clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W15B	1100	6000	aluminium, double (air), clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
W17	800	3400	aluminium, double (air), clear	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed
East facing					
W03	1800	1200	aluminium, double (air), clear	eave 300 mm, 700 mm above head of window or glazed door	not overshadowed
W04	1800	1200	aluminium, double (air), clear	eave 300 mm, 830 mm above head of window or glazed door	not overshadowed
W05	3500	1200	aluminium, double (air), clear	eave 450 mm, 150 mm above head of window or glazed door	not overshadowed
W16	950	1100	aluminium, double (air), clear	eave 450 mm, 150 mm above head of window or glazed door	not overshadowed
South facing					
W06	2100	2400	aluminium, double (air), clear	eave 150 mm, 450 mm above head of window or glazed door	not overshadowed
W07	1200	1600	aluminium, double (air), clear	verandah 4500 mm, 1700 mm above base of window or glazed door	not overshadowed
D03	2100	1900	aluminium, double (air), clear	verandah 4500 mm, 2550 mm above base of window or glazed door	not overshadowed
D04	2100	3600	aluminium, double (air), clear	verandah 4500 mm, 2550 mm above base of window or glazed door	not overshadowed
D05	2100	820	aluminium, double (air), clear	eave 450 mm, 1100 mm above head of window or glazed door	not overshadowed
W08	1500	600	aluminium, double (air), clear	eave 450 mm, 1100 mm above head of window or glazed door	not overshadowed
W09	1500	1800	aluminium, double (air), clear	eave 450 mm, 1100 mm above head of window or glazed door	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
W10	1500	1500	aluminium, double (air), clear	eave 450 mm, 900 mm above head of window or glazed door	not overshadowed
West facing					
W11	1500	1200	aluminium, double (air), clear	eave 450 mm, 860 mm above head of window or glazed door	not overshadowed
w14	950	1100	aluminium, double (air), clear	eave 450 mm, 200 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: electric storage.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans + 1-phase airconditioning; Energy rating: 8 star (cold zone)		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans + 1-phase airconditioning; Energy rating: 8 star (cold zone)		v	~
The cooling system must provide for day/night zoning between living areas and bedrooms.		v	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 8 star (cold zone)		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 8 star (cold zone)		~	~
The heating system must provide for day/night zoning between living areas and bedrooms.		 Image: A set of the set of the	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		~	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A second s	v
Laundry: natural ventilation only, or no laundry; Operation control: n/a		~	~
Artificial lighting			-
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
 at least 4 of the bedrooms / study; dedicated 		 Image: A second s	~

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
 at least 2 of the living / dining rooms; dedicated 		~	~
the kitchen; dedicated		_	~
all bathrooms/toilets; dedicated			
the laundry; dedicated			j.
all hallways; dedicated		V	
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 6 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 8 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.	~	~	~
Other			
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.