

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1390075S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 02 May 2023

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary			
Project name	Serviced Apartment 2 - 2023		
Street address	713 Black Springs Road Budgee Budgee 2850		
Local Government Area	Mid-Western Regional Council		
Plan type and plan number	deposited 755429		
Lot no.	41		
Section no.	-		
Project type	separate dwelling house - secondary dwelling		
No. of bedrooms	2		
Project score			
Water	√ 63 Target 30		
Thermal Comfort	✓ Pass Target Pass		
Energy	√ 40 Target 40		

Certificate Pro	epared by
-----------------	-----------

Name / Company Name: Amanda Buckley

ABN (if applicable): N/A

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 1/9

Description of project

Project address				
Project name	Serviced Apartment 2 - 2023			
Street address	713 Black Springs Road Budgee Budgee 2850			
Local Government Area	Mid-Western Regional Council			
Plan type and plan number	Deposited Plan 755429			
Lot no.	41			
Section no.	-			
Project type				
Project type	separate dwelling house - secondary dwelling			
No. of bedrooms	2			
Site details				
Site area (m²)	165000			
Roof area (m²)	88			
Conditioned floor area (m2)	65.0			
Unconditioned floor area (m2)	8.0			
Total area of garden and lawn (m2)	0			
Roof area (m2) of the existing dwelling	158			
No. of bedrooms in the existing dwelling	2			

Assessor details and thermal lo	ads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	✓ 63	Target 30
Thermal Comfort	✓ Pass	Target Pass
Energy	4 0	Target 40

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 2/9

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		V	V
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		V	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		V	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 22900 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	V	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 88 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		V	~
The applicant must connect the rainwater tank to:			
all toilets in the development		V	V
the cold water tap that supplies each clothes washer in the development		~	-
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	V
all hot water systems in the development			
• all indoor cold water taps (not including taps that supply clothes washers) in the development			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 3/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	~	-
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	V	V	V
The dwelling must not contain third level habitable attic room.	V	~	-
Floor, walls and ceiling/roof	1		<u>'</u>
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	<u> </u>	V

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - framed (weatherboard, fibre cement, metal clad)	3.20 (or 3.60 including construction)	
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 5 (up), roof: foil backed blanket (55 mm)	framed; dark (solar absorptance > 0.70)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 4/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check		
Windows, glazed doors and skylights					
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	→	~		
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	V	~	V		
The following requirements must also be satisfied in relation to each window and glazed door:	V	~	V		
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-		
- Aluminium single clear					
- Aluminium double (air) clear					
- Timber/uPVC/fibreglass single clear					
- Timber/uPVC/fibreglass double (air) clear					
• Overshadowing buildings/vegetation must be of the height and distance from the centre and the base of the window and glazed door, as specified in the 'overshadowing' column.	V	~	V		

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North-East facing					
TFG-1823 W-16	1800	2350	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
TFG-1823 W-15	1800	2350	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	not overshadowed
SW-2112 W-10	2100	1210	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	2-4 m high, 8-12 m away
SW-2112 W-11	2100	1210	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	2-4 m high, 8-12 m away
South-East facing	·				
FG-0618 W-12	600	1800	aluminium, single, clear	none	not overshadowed
SW-2124-W13	2100	2410	aluminium, single, clear	none	2-4 m high, 5-8 m away

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 5/9

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
South-West facing					
SW-0618 W-14	600	1800	aluminium, single, clear	eave 600 mm, 340 mm above head of window or glazed door	2-4 m high, 8-12 m away
North-West facing					
SW-2124 W-09	2100	2410	aluminium, single, clear	none	>4 m high, 8-12 m away

Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 6/9

BASIX

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	~	✓	-
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans + 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		→	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans + 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		~	~
The cooling system must provide for day/night zoning between living areas and bedrooms.		~	-
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		→	
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: EER 3.5 - 4.0		y	V
The heating system must provide for day/night zoning between living areas and bedrooms.		~	-
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		→	V
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	V
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		V	V
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 2 of the bedrooms / study; dedicated			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
at least 1 of the living / dining rooms; dedicated		V	~
• the kitchen; dedicated		~	V
all bathrooms/toilets; dedicated		•	V
the laundry; dedicated		•	V
all hallways; dedicated		✓	V
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	→	V
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	V
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		✓	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed indoor or sheltered clothes drying line as part of the development.			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 8/9

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_20_0 Certificate No.: 1390075S Tuesday, 02 May 2023 page 9/9