

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1404264S_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Tuesday, 08 August 2023

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary		10年7年	
Project name	23081_161 Eurund	leree Lane_02	
Street address	161 Eurunderee La	ine Eurunderee 2850	
Local Government Area	Mid-Western Region	nal Council	
Plan type and plan number	deposited 755418		
Lot no.	13		
Section no.	and a		
Project type	separate dwelling house		
No. of bedrooms	2		
Project score		MATERIAL STATES	
Water	✓ 38	Target 30	
Thermal Comfort	✓ Pass	Target Pass	
Energy	✓ 40	Target 40	

Certificate Prepared by	
Name / Company Name: Marc Kiho	
ABN (if applicable): 99309889330	

Description of project

Project name	23081_161 Eurunderee Lane_02	
Street address	161 Eurunderee Lane Eurunderee 2850	
Local Government Area	Mid-Western Regional Council	
Plan type and plan number	Deposited Plan 755418	
Lot no.	13	
Section no.		
Project type	A LANGUAGE STATE OF THE STATE OF	
Project type	separate dwelling house	
No. of bedrooms	2	
Site details	A THE PARTY OF THE	
Site area (m²)	2000	
Roof area (m²)	150	
Conditioned floor area (m2)	72.0	
Unconditioned floor area (m2)	8.0	
Total area of garden and lawn (m2)	200	

Assessor details and thermal	loads	S. D. M. C. C.
Assessor number	n/a	MARINE MARINE
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		40 MARINE
Water	✓ 38	Target 30
Thermal Comfort	✓ Pass	Target Pass
Energy	✔ 40	Target 40

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifie
Fixtures The Control of the Control			
The applicant must install showerheads with a minimum rating of 3 star (> 7.5 but <= 9 L/min) in all showers in the development.			
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		•	~
			U
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.			
		~	
he applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.			
Alternative water		~	
AICHIDATVE WATCH			
Rainwater tank			
he applicant must install a rainwater tank of at least 5000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.		_	
he applicant must configure the rainwater tank to collect rain runoff from at least 150 square metres of the roof area of the levelopment (excluding the area of the roof which drains to any stormwater tank or private dam).			
he applicant must connect the rainwater tank to:			•
all toilets in the development			
 the cold water tap that supplies each clothes washer in the development 			•
		✓	~
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 			
all hot water systems in the development		•	~
			-
 all indoor cold water taps (not including taps that supply clothes washers) in the development 		•	•
			-

Planning, Industry & Environment www.basix.nsw.gov.au

BASIX

Version: 3.0 / DARWINIA_3_20_0

Tuesday, 08 August 2023

Certificate No.: 1404264S_02

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier
General features			
The dwelling must not have more than 2 storeys.			
The conditioned floor area of the develling and the	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.			
The dwelling must not contain open mezzanine area exceeding 25 square metres.		•	~
The dwelling must not contain third level habitable attic room.	~	~	~
The dwelling must not contain tring level nabitable attic room.		J	u
Floor, walls and ceiling/roof		A STATE OF THE PARTY OF THE PAR	
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table		ALL THE RELAKE	
pelow.	~		

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	Other specifications
external wall - framed (weatherboard, fibre cement, metal clad)	2.20 (or 2.60 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4 (up), roof: foil/sarking	Unventilated: medium (color cheersters 2, 475, 2, 70)
ceiling and roof - raked ceiling / pitched or skillion roof, framed	ceiling: 4 (up), roof: foil/sarking	unventilated; medium (solar absorptance 0.475-0.70) framed; medium (solar absorptance 0.475-0.70)

Note	 Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	 In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Certificate No.: 1404264S_02

BASIX

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights		Name of Street	SECTION.
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	_	~	-
The following requirements must also be satisfied in relation to each window and glazed door: • For the following glass and frame types, the certifier check can be performed by visual inspection.		~	~
- Aluminium single clear			•
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
Bed 1	2000	1800	aluminium, single, clear	solid overhang 1800 mm, 200 mm above head of window or glazed door	not overshadowed
Living	2000	1800	aluminium, single, clear	solid overhang 1800 mm, 200 mm above head of window or glazed door	not overshadowed
Bath	1200	800	aluminium, single, clear	none	not overshadowed
Dining	1200	800	aluminium, single, clear	none	not overshadowed
East facing					
Dining	1200	800	aluminium, single, clear	solid overhang 7500 mm, 200 mm above head of window or glazed door	not overshadowed
Bed 1	1500	800	aluminium, single, clear	none	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
Bed 2	1500	800	aluminium, single, clear	none	not overshadowed
South facing				RESTRICTED TO THE STATE OF THE	not overstiadowed
Entry	2000	1600	aluminium, single, clear	solid overhang 1700 mm, 450 mm above head of window or glazed door	not overshadowed
Kitchen	1500	800	aluminium, single, clear	none	not overshadowed
Bed 2	1500	800	aluminium, single, clear	none	The Port of the Control of the Contr
West facing					not overshadowed
Bath	2000	800	aluminium, single, clear	solid overhang 3300 mm, 450 mm above head of window or glazed door	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	~	~	_
Cooling system		MARKET AND SE	THE REAL PROPERTY.
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	_
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		~	-
Heating system	74 07	TO THE WAY TO SEE	The state of the s
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: wood heater; Energy rating: n/a		_	J
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	_
The wood heater must have a compliance plate confirming that it complies with the relevant Australian standards, and must be installed in accordance with the requirements of all applicable regulatory authorities.			~
Ventilation Ventilation		A STATE OF	Sale III
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	~
Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off		V	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
 at least 2 of the bedrooms / study; dedicated 			
• at least 2 of the living / dining reams; dedicated		~	~
at least 2 of the living / dining rooms; dedicated			

Planning, Industry & Environment www.basix.nsw.gov.au

BASIX

Version: 3.0 / DARWINIA_3_20_0

Tuesday, 08 August 2023

Certificate No.: 1404264S_02

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
the kitchen; dedicated			1
all bathrooms/toilets; dedicated		•	•
the laundry; dedicated		~	~
all hallways; dedicated		~	~
		~	-
Natural lighting			770792
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.			112767
The applicant must install a window and/or skylight in 1 hothroom/o/wailaw	~	~	~
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	_	_	V
Other Control of the	AND REAL PROPERTY.		
he applicant must install an induction cooktop & electric oven in the kitchen of the dwelling.		S. A. L. W. C. L. S.	
		~	
he applicant must install a fixed outdoor clothes drying line as part of the development.			
he applicant must install a fixed indoor or sheltered clothes drying line as part of the development.		~	
and as part of the development.		J	

Planning, Industry & Environment www.basix.nsw.gov.au

BASIX

Version: 3.0 / DARWINIA_3_20_0

Certificate No. 1404264S_02

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a 🧹 in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a 📦 in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vin the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.