


The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.

IF IN DOUBT, ASK.



FOUNDATION PLAN AND MEMBER LAYOUT
SCALE: 1 = 100

DO NOT SCALE THIS DRAWING. USE FIGURED DIMENSIONS ONLY. ALL DIMENSIONS TO BE VERIFIED ON SITE.

MEMBER LEGEND

C1	C15012
C2	C15019

1 OF 7
SHEET
JOB NO. LGOW/13157
DATE 30/1/2024
CHECKED TM
DRAWN FDB


STEEL BUILDING BY (CONTACT)
FAIR DINKUM BUILDS LITHGOW
02 63524444
HARRISON GROSVENOR
162 GLADSTONE STREET
MUDGEE




NORTHERN CONSULTING engineers
Civil & Structural Engineers
50 Punari Street
Currajong, Qld 4812
Fax: 07 4725 5850
Email: design@nceng.com.au
ABN 341 008 173 56

Mr T [Redacted] st RPEQ
Sign [Redacted]
Date 30/1/2024
Registered on the NPER in the areas of practice of Civil & Structural National Professional Engineers Register


The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.




1 SIDEWALL EXTERIOR ELEVATION
2 SCALE: 1 = 100



2 SIDEWALL EXTERIOR ELEVATION
2 SCALE: 1 = 100



4 ENDWALL INTERIOR ELEVATION
2 SCALE: 1 = 100



3 ENDWALL INTERIOR ELEVATION
2 SCALE: 1 = 100

DIAGONAL X BRACING NOT REQUIRED IN THIS BUILDING.
CLADDING DIAPHRAGM SUFFICIENT.

2 OF 7	SHEET	JOB NO. LGOW/13157	DATE 30/1/2024	CHECKED TM	DRAWN FDB
	STEEL BUILDING BY (CONTACT) FAIR DINKUM BUILDS LITHGOW 02 63524444 HARRISON GROSVENOR 162 GLADSTONE STREET MUDGEE				

FOR AT






Civil & Structural Engineers
 50 Punari Street
 Currajong, Qld 4812
 Fax: 07 4725 5850
 Email: design@nceng.com.au
 ABN 341 008 173 56

Registered Chartered Professional Engineer
 Registered Professional Engineer (Civil & Structural) QLD
 Registered Certifying Engineer (Structural) N.T.
 Registered Engineer - (Civil) VIC
 Registered Engineer - (Civil) TAS

Regn. No. 2558980
 Regn. No. 9985
 Regn. No. 116373ES
 Regn. No. PE0002216
 Regn. No. CC5648M


Mr Timo [Redacted] Just RPEQ

Signature [Redacted]

Date 30/1/2024

Registered on the NPER in the areas of practice of Civil & Structural National Professional Engineers Register

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.



1
3 INTERNAL FRAME SECTION
SCALE: 1 = 50

3 OF 7
SHEET
JOB NO. LGOW/13157
DATE 30/1/2024
CHECKED TM
DRAWN FDB

STEEL BUILDING BY (CONTACT)
FAIR DINKUM BUILDS LITHGOW
02 63524444
HARRISON GROSVENOR
162 GLADSTONE STREET
MUDGEE



NORTHERN CONSULTING engineers
Civil & Structural Engineers
50 Punari Street
Currajong, Qld 4812
Fax: 07 4725 5850
Email: design@nceng.com.au
ABN 341 008 173 56

Registered Chartered Professional Engineer
Registered Professional Engineer (Civil & Structural) QLD
Registered Certifying Engineer (Structural) N.T.
Registered Engineer - (Civil) VIC
Registered Engineer - (Civil) TAS

Regn. No. 2558980
Regn. No. 9985
Regn. No. 116373ES
Regn. No. PE0002216
Regn. No. CC5648M

Mr T
Sign
Date 30/1/2024
Registered on the NPER in the areas of practice of Civil & Structural National Professional Engineers Register

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.

STRUCTURAL GENERAL NOTES


- GOVERNING CODE** : NATIONAL CONSTRUCTION CODE (NCC), LOADING TO AS1170 - ALL SECTIONS. BUILDING SUITABLE AS EITHER A PRIVATE GARAGE CLASS 10a, OR A FARM SHED (CLASS 7 OR 8), UNLESS OTHERWISE SPECIFICALLY NOTED. FOR USE AS A FARM SHED, IT MUST MEET THE FOLLOWING REQUIREMENTS:
 - BE LESS THAN 2000 SQM IN AREA (INCLUSIVE OF ANY MEZZANINE FLOOR AREA).
 - MUST BE LOCATED ON A FARM AND USED IN CONNECTION WITH FARMING PURPOSES.
 - BUILDING IS NOT TO BE OCCUPIED FREQUENTLY NOR FOR EXTENDED PERIODS BY PEOPLE, WITH A MAXIMUM OF 1 PERSON PER 200 SQM OR 2 PERSONS MAXIMUM IN TOTAL WHICHEVER IS THE LESSER.
- DRAWING OWNERSHIP** : THESE DRAWINGS REMAIN THE PROPERTY OF FBHS (AUST) PTY LIMITED. ENGINEERING SIGNATURE AND CERTIFICATION IS ONLY VALID WHEN BUILDING IS SUPPLIED BY A DISTRIBUTOR OF FBHS. DRAWINGS ARE PROVIDED FOR THE DUAL PURPOSE OF OBTAINING BUILDING PERMITS AND AIDING CONSTRUCTION. ANY OTHER USE OR REPRODUCTION IS PROHIBITED WITHOUT WRITTEN APPROVAL FROM FBHS.
- DRAWING SIGNATURE REQUIREMENTS** : THESE DRAWINGS ARE NOT VALID UNLESS SIGNED BY THE ENGINEER. THE ENGINEER ACCEPTS NO LIABILITY OR RESPONSIBILITY FOR DRAWINGS WITHOUT A SIGNATURE. EACH TITLE BLOCK CONTAINS A WATER MARK UNDER THE CUSTOMERS NAME CONTAINING THE DATE OF PRODUCTION OF THE DRAWINGS; THE DRAWINGS ARE TO BE SUBMITTED TO COUNCIL WITHIN 21 DAYS OF THIS DATE. THIS IS TO ENSURE THAT ONLY CURRENT DRAWINGS ARE IN CIRCULATION.
- CONTRACTOR RESPONSIBILITIES** : CERTIFIER AND CONTRACTOR TO CONFIRM (ON SITE) THAT THE WIND LOADINGS APPLIED TO THIS DESIGN ARE TRUE AND CORRECT FOR THE ADDRESS STATED IN THE TITLE BLOCK. CONTRACTOR SHALL VERIFY AND CONFIRM ALL EXISTING CONDITIONS AND DIMENSIONS. ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES BETWEEN DRAWINGS AND EXISTING CONDITIONS PRIOR TO START OF WORK. CONTRACTOR MUST NOT MAKE ANY DEVIATION FROM THE PROVIDED PLANS WITHOUT FIRST OBTAINING WRITTEN APPROVAL FROM ONE OF THE UNDERSIGNING ENGINEERS. THE ENGINEER / FBHS TAKE NO RESPONSIBILITY FOR CHANGES MADE WITHOUT WRITTEN APPROVAL. CONTRACTOR IS RESPONSIBLE FOR ENSURING NO PART OF THE STRUCTURE BECOMES OVERSTRESSED DURING CONSTRUCTION. BUILDING IS NOT STRUCTURALLY ADEQUATE UNTIL THE INSTALLATION OF ALL COMPONENTS AND DETAILS SHOWN IS COMPLETED IN ACCORDANCE WITH THESE DRAWINGS. THE INDICATED DRAWING SCALES ARE APPROXIMATE. DO NOT SCALE DRAWINGS FOR CONSTRUCTION PURPOSES. FOR FURTHER DIRECTIONS ON CONSTRUCTION THE CONTRACTOR SHOULD CONSULT THE APPROPRIATE INSTRUCTION MANUAL.
- ENGINEERING** : THE ENGINEER / FBHS ARE NOT ACTING AS PROJECT MANAGERS FOR THIS DEVELOPMENT, AND WILL NOT BE PRESENT DURING CONSTRUCTION. THE UNDERSIGNING ENGINEERS HAVE REVIEWED THIS BUILDING FOR CONFORMITY ONLY TO THE STRUCTURAL DESIGN PORTIONS OF THE GOVERNING CODE. THE PROJECT MANAGER IS RESPONSIBLE FOR ADDRESSING ANY OTHER CODE REQUIREMENTS APPLICABLE TO THIS DEVELOPMENT. THESE DOCUMENTS ARE STAMPED ONLY AS TO THE COMPONENTS SUPPLIED BY FBHS. IT IS THE RESPONSIBILITY OF THE PURCHASER TO COORDINATE DRAWINGS PROVIDED BY FBHS WITH OTHER PLANS AND/OR OTHER COMPONENTS THAT ARE PART OF THE OVERALL PROJECT. IN CASES OF DISCREPANCIES, THE LATEST DRAWINGS PROVIDED BY FBHS SHALL GOVERN. NO ALTERATIONS TO THIS STRUCTURE (INCLUDING REMOVAL OF CLADDING) ARE TO BE UNDERTAKEN WITHOUT THE CONSENT OF THE CERTIFYING ENGINEER. OPENINGS SUCH AS WINDOWS AND DOORS NEED TO BE INSTALLED AS PER THE PRODUCT MANUFACTURER'S INFORMATION/DETAILS. THE BUILDING IS DESIGNED AS A STAND-ALONE BUILDING, NOT RELYING ON ANY ADJACENT BUILDING. IF THE PERMANENT OPENING IS OBSTRUCTED BY ANY ADJACENT BUILDING AND WITHIN A DISTANCE OF 0.5M OF SAID OPENING, THE DESIGN SHOULD BE REFERRED TO THE DESIGN ENGINEER FOR REVIEW OF INTERNAL PRESSURES AND POSSIBLE REDESIGN.
- INSPECTIONS** : NO SPECIAL INSPECTIONS ARE REQUIRED BY THE GOVERNING CODE ON THIS JOB. ANY OTHER INSPECTIONS REQUESTED BY THE LOCAL BUILDING DEPARTMENT SHALL BE CONDUCTED AT THE OWNER'S EXPENSE.
- SOIL REQUIREMENTS** : SITE CLASSIFICATION TO BE A, S OR M ONLY. SOIL SAFE BEARING CAPACITY VALUE INDICATED ON DRAWING SHEET 4 OCCURS AT 100mm BELOW FINISH GRADE, EXISTING NATURAL GRADE, OR AT FROST DEPTH SPECIFIED BY LOCAL BUILDING DEPARTMENT, WHICHEVER IS THE LOWEST ELEVATION. REGARDLESS OF DETAIL Y ON SHEET 4 THE MINIMUM FOUNDATION DEPTH SHOULD BE 100MM INTO NATURAL GROUND OR BELOW FROST DEPTH SPECIFIED BY LOCAL COUNCIL. ROLLED OR COMPACTED FILL MAY BE USED UNDER SLAB, COMPACTED IN 150mm LAYERS TO A MAXIMUM DEPTH OF 900mm. CONCRETE FOUNDATION EMBEDMENT DEPTHS DO NOT APPLY TO LOCATIONS WHERE ANY UNCOMPACTED FILL OR DISTURBED GROUND EXISTS OR WHERE WALLS OF THE EXCAVATION WILL NOT STAND WITHOUT SUPPLEMENTAL SUPPORT, IN THIS CASE SEEK FURTHER ENGINEERING ADVICE.
- CLASS 10a or Class 7 FOOTING DESIGNS** : THE FOUNDATION DOCUMENTED IS ALSO APPROPRIATE FOR CLASS 10a or CLASS 7 BUILDING DESIGNS ON 'M-D', 'H', 'H-D' OR 'E' CLASS SOILS, IF TOTAL SLAB AREA IS UNDER 100m SQUARE AND THE MAXIMUM SLAB DIMENSION (LENGTH AND WIDTH) IS LESS THAN OR EQUAL TO 12m. PLEASE BE AWARE THAT THE SLAB DESIGN FOR H & E CLASS SOILS IN THESE INSTANCES ARE DESIGNED TO EXPERIENCE SOME CRACKING. THIS CRACKING IS NOT CONSIDERED A STRUCTURAL FLAW OR DESIGN ISSUE, AND IS SIMPLY COSMETIC IN NATURE. IF THIS IS A CONCERN TO THE CLIENT IT IS ADVISED THEY DISCUSS OTHER OPTIONS WITH THE RELEVANT DISTRIBUTOR PRIOR TO THE POURING OF THE SLAB.
- CONCRETE REQUIREMENTS** : ALL CONCRETE DETAILS AND PLACEMENT SHALL BE PERFORMED IN ACCORDANCE WITH AS2870 AND AS3600. CONCRETE SHALL HAVE A MIN. 28-DAY STRENGTH OF 20MPa FOR EXPOSURE A1, 25MPa FOR EXPOSURE A2, 32MPa FOR EXPOSURE B1, 40MPa FOR EXPOSURE B2 AND 50MPa FOR EXPOSURE C, IN ACCORDANCE WITH SECTION 4, AS3600. CEMENT TO BE TYPE A. MAX AGGREGATE SIZE OF 20mm. SLUMP TO BE 80mm +/-15mm. SLABS TO BE CURED FOR 7 DAYS BY WATERING OR COVERING WITH A PLASTIC MEMBRANE, AFTER WHICH CONSTRUCTION CAN BEGIN, DUE CARE GIVEN NOT TO OVER-TIGHTEN HOLD DOWN BOLTS. GIVEN ALLOWABLE SOIL TYPES 1 LAYER OF SL72 REINFORCING MESH IS TO BE INSTALLED ON STANDARD SLABS WITH A MINIMUM 30MM COVER FROM CONCRETE SURFACE. CONCRETE REINFORCING TO CONFORM TO AS 1302, AS1303 & AS 1304. ALL REINFORCING COVER TO BE A MINIMUM OF 30mm.
- STRUCTURAL STEEL REQUIREMENTS** : ALL STRUCTURAL STEEL, INCLUDING SHEETING THOUGH EXCLUDING CONCRETE REINFORCING, SHALL CONFORM TO AS 1397 (GAUGE <= 1mm fy = 550MPa, GAUGE > 1mm < 1.5mm fy = 500MPa, GAUGE >= 1.5mm fy = 450MPa). NO WELDING IS TO BE PERFORMED ON THIS BUILDING. ALL STRUCTURAL MEMBERS AND CONNECTIONS DESIGNED TO AS4600. ALL BOLT HOLE DIAMETERS TO STRAIT GENERAL FINCHINGS.
- FOOT TRAFFIC** : FOR ERECTION AND MAINTENANCE PLEASE NOTE THE FOLLOWING DEFINED FOOT TRAFFIC ZONES:
 - CORRUGATED: WALK ONLY WITHIN 200MM OF SCREW LINES. FEET SPREAD OVER AT LEAST TWO RIBS.
 - MONOCLAD: WALK ONLY IN PANS, OR ON RIBS AT SCREW LINES.

PROJECT DESIGN CRITERIA	
ROOF LIVE LOAD:	0.25 kPa
BASIC WIND SPEED:	VR 45 m/s
SITE WIND SPEED:	VsitB 32.8 m/s
WIND REGION:	Reg A3
TOPOGRAPHY FACTOR, Mt:	1
SHIELDING FACTOR, Ms:	0.85
MAX GROUND SNOW LOAD:	N/A
MAX ROOF SNOW LOAD:	N/A
SITE ALTITUDE:	N/A
TERRAIN CATEGORY:	TCat 2.67
SOIL SAFE BEARING CAPACITY:	100 kPa
RETURN PERIOD:	1:500
LIMITING CPI 1:	-0.58
LIMITING CPI 2:	0.64
IMPORTANCE LEVEL:	2

DETAIL KEYS	
DK1	ENDWALL VERTICAL MULLION (SEE DETAIL C/5 FOR TOP CONN. AND F/5 FOR BASE CONN.)
DK2	FLYBRACING PER DETAIL L/5
DK3	X-BRACING IN ROOF ABOVE (SEE DETAIL M/5)
DK4	DOUBLE X-BRACING IN ROOF ABOVE (SEE DETAIL M/5)


SCHEDULE OF OPENINGS						
DOOR	OPENING WIDTH	SIZE MAX HEIGHT	OPENING TYPE	HEADER GIRT	OPENING JAMBS	WIND RATED
①	3090	2580*	2.80H X 3.15 CB "SERIES A #"	SINGLE	Z15012P	NO
②	3090	2580*	2.80H X 3.15 CB "SERIES A #"	SINGLE	Z15012P	NO
③	3090	2580*	2.80H X 3.15 CB "SERIES A #"	SINGLE	Z15012P	NO
④	820	2040	EXTERNAL PA DOOR 180 DEG	SINGLE		YES

NOTES: 1) SEE SHEET 5 FOR DOOR OPENING FRAMING INFORMATION.
 2) ALL DOOR SCHEDULE MEASUREMENTS ARE ACTUAL DOOR/WINDOW SIZE NOT OPENING SIZE.
 * ROLLER DOOR OPENING HEIGHT DEPENDENT ON FINAL BUILD LOCATION.



SHEET <div style="font-size: 2em; font-weight: bold;">4</div> OF <div style="font-size: 2em; font-weight: bold;">7</div>	JOB NO. LGOW/13157	DATE 30/1/2024	CHECKED TM	DRAWN FDB	STEEL BUILDING BY (CONTACT) <div style="text-align: center; font-weight: bold; font-size: 1.2em;"> FAIR DINKUM BUILDS LITHGOW 02 63524444 HARRISON GROSVENOR 162 GLADSTONE STREET MUDGEE </div>	 	 Civil & Structural Engineers 50 Punari Street Currarjong, Qld 4812 Fax: 07 4725 5850 Email: design@nceng.com.au ABN 341 008 173 56	Mr Timot Signature Date 30/1/2024 Registered on the NPER in the areas of practice of Civil & Structural National Professional Engineers Register
---	-----------------------	-------------------	---------------	--------------	--	------	---	---

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.



MEMBER AND MATERIAL SCHEDULE

1	END WALL RAFTER	Single C15012
2	C.S. FRAME RAFTER	Single C15015
3	END FRAME COLUMN (C1)	Single C15012
4	C.S. FRAME COLUMN (C2)	Single C15019
5	MULLION (C3)	Single C15015
6	C.S. FRAME KNEE BRACE	Single C10010 @ 1.69 LONG 2 bolts each end
7	KNEE BRACE HEIGHT UP COLUMN	1.99m
8	KNEE BRACE LENGTH UP RAFTER	1.06m
9	C.S. FRAME APEX BRACE	Single C10010 @ 2.10 LONG 2 bolts each end
10	APEX POSITION FROM RAFTER END	1.05m
11	ANCHOR BOLTS (# PER DETS.)	Screw Anchor 12mm x 100 Galv
12	EAVE PURLIN	C10010 (Eave Purlin Bracket 0mm from top of column)
13	TYP. ROOF PURLIN SIZE	Z10010
14	MAIN BLDG. PURLIN SPACING	0.865 m. (4 rows) (Max Allow. 0.999m)
15	MAIN BLDG. PURLIN LENGTH	4.4 m. (0.4m Overlap)
16	TYP. SIDEWALL GIRT SIZE	Z10010 (1 rows of bridging)
17	MAIN BLDG. SIDEWALL GIRT SPACING	1.349 m. (2 rows) (Max Allow. 1.799m)
18	MAIN BLDG. SIDEWALL GIRT LENGTH	4.4 m. (0.4m Overlap)
19	SIDEWALL GIRT BRIDGING	Tophat 64 x 0.75
20	TYP. ENDWALL GIRT SIZE	Z10010 (1 rows of bridging)
21	MAIN BLDG. ENDWALL GIRT SPACING	1.640 m. (2 rows) (Max Allow. 1.799m)
22	MAIN BLDG. ENDWALL GIRT LENGTH	3.35 m. (0.1m Overlap)
23	ENDWALL GIRT BRIDGING	Tophat 64 x 0.75
24	FRAME SCREW FASTENERS	14-13x22 Hex C/S (SP HD 5/16" Hex Drive)
25	FRAME BOLT FASTENERS	Purlin Assy M12x30 Z/P
26	X-BRACING STRAP AND FASTENERS	None required for this building. Cladding Diaphragm Sufficient.
27	WALL COLOUR	CLASSIC_CREAM
28	ROOF COLOUR	PALE_EUCALYPT
29	ROLLER DOOR COLOUR	PALE_EUCALYPT
30	P.A. DOOR COLOUR	PALE_EUCALYPT
31	DOWNPIPE COLOUR	PALE_EUCALYPT
32	GUTTER COLOUR	PALE_EUCALYPT
33	CORNER FLASHING COLOUR	PALE_EUCALYPT
34	BARGE FLASHING COLOUR	PALE_EUCALYPT
35	OPENING FLASHING COLOUR	PALE_EUCALYPT
36	OPEN BAY HEADER HEIGHT	0.5

"C.S." = CLEARSPAN "L." = LEFT "R." = RIGHT

5 OF 7 SHEET
 JOB NO. LGOW13157
 DATE 30/1/2024
 CHECKED TM
 DRAWN FDB

STEEL BUILDING BY (CONTACT)
FAIR DINKUM BUILDS LITHGOW
 02 63524444
HARRISON GROSVENOR
 162 GLADSTONE STREET
 MUDGEE




NORTHERN CONSULTING engineers
 Civil & Structural Engineers
 50 Punari Street
 Currarong, Qld 4812
 Fax: 07 4725 5850
 Email: design@nceng.com.au
 ABN 341 008 173 56

Registered Chartered Professional Engineer
 Registered Professional Engineer (Civil & Structural) QLD
 Registered Certifying Engineer (Structural) N.T.
 Registered Engineer - (Civil) VIC
 Registered Engineer - (Civil) TAS


Regn. No. 2558980
 Regn. No. 9985
 Regn. No. 116373ES
 Regn. No. PE0002216
 Regn. No. CC5648M

Mr Timot [Redacted] Aust RPEQ
 Signature [Redacted]
 Date 30/1/2024
 Registered on the NPER in the areas of practice
 of Civil & Structural National Professional
 Engineers Register


The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.




1
6 SIDEWALL EXTERIOR ELEVATION
SCALE: 1 = 100



2
6 SIDEWALL EXTERIOR ELEVATION
SCALE: 1 = 100



4
6 ENDWALL EXTERIOR ELEVATION
SCALE: 1 = 100



3
6 ENDWALL EXTERIOR ELEVATION
SCALE: 1 = 100

BUILDING COLOURS

WALL	CLASSIC CREAM
ROOF	PALE EUCALYPT
ROLLER DOOR	PALE EUCALYPT
P.A. DOOR	PALE EUCALYPT
DOWNPIPE	PALE EUCALYPT
GUTTER	PALE EUCALYPT
	PALE EUCALYPT
	PALE EUCALYPT

6
OF
7

SHEET

JOB NO.
LGOW13157

DATE
30/1/2024

CHECKED
TM

DRAWN
FDB

STEEL BUILDING BY (CONTACT)
FAIR DINKUM BUILDS LITHGOW
02 63524444
HARRISON GROSVENOR
162 GLADSTONE STREET
MUDGEE

FOR
AT



fair
dinkum
builds™

NORTHERN CONSULTING engineers

Civil & Structural Engineers
50 Punari Street
Currarong, Qld 4812
Fax: 07 4725 5850
Email: design@nceng.com.au
ABN 341 008 173 56

Registered Chartered Professional Engineer
Registered Professional Engineer (Civil & Structural) QLD
Registered Certifying Engineer (Structural) N.T.
Registered Engineer - (Civil) VIC
Registered Engineer - (Civil) TAS

Regn. No. 2558980
Regn. No. 9985
Regn. No. 116373ES
Regn. No. PE0002216
Regn. No. CC5648M

Mr [Redacted] Just RPEQ

Sig [Redacted]

Date 30/1/2024

Registered on the NPER in the areas of practice
of Civil & Structural National Professional
Engineers Register

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.

GUIDE TO THE INSTALLATION OF TEMPORARY BRACING

(REFER TO INSTALLATION GUIDE MANUAL FOR THE TWO METHODS OF CONSTRUCTION)

NOTES:

BRACING MATERIALS - THE SHED ERECTOR TO SUPPLY SPECIFIC BRACING. SUITABLE RIGID MEMBERS CAPABLE OF TENSION AND COMPRESSION OR OPPOSING CHAINS OR OPPOSING LOAD RATED RATCHET STRAPS TO BE USED. (RIGID BRACING AS SHOWN ON DIAGRAM) ROPE BRACING SUITABLE ONLY FOR SMALLER STRUCTURES IN IDEAL CONDITIONS.

BRACING LOCATION - TEMPORARY BRACING TO BE ERECTED AS CLOSE TO 45 DEGREE ANGLE AND FIXED TO THE TOP OF THE COLUMN OR MULLION TO ACHIEVE THE OPTIMUM EFFECTIVENESS. IF THERE IS NOT ENOUGH SPACE FOR A 45 DEGREE ANGLE, THEN 20 DEGREE ANGLE IS TO BE THE MINIMUM ANGLE ALLOWED (REFER TO DIAGRAM). RIGID TEMPORARY BRACING MEMBER TO BE BOLTED TO HEAVY ANGLE PEGS HAMMERED INTO THE GROUND OR TO A BRACKET, MASONRY ANCHORED TO THE SLAB.

BRACING REMOVAL - TEMPORARY BRACING TO REMAIN IN PLACE UNTIL CLADDING IS FULLY INSTALLED WHERE POSSIBLE. IN NO CASE SHOULD TEMPORARY BRACING BE REMOVED UNTIL ALL PURLINS, GIRTS (AND PERMANENT CROSS BRACING WHERE USED) ARE FIXED.

SITE SAFETY - DUE CONSIDERATION TO BE GIVEN TO SITE SAFETY IN REGARD TO LOCATIONS OF BRACING AND PEGS.


GUIDE APPLICATION - TEMPORARY BRACING AS DESCRIBED IS A MINIMUM REQUIREMENT FOR AN AVERAGE, STANDARD SITE CONDITION. PROVIDE ADDITIONAL BRACING FOR MORE SEVERE AND/OR HIGH EXPOSURE SITE CONDITIONS. ADDITIONAL BRACING TO BE USED AS AND WHERE NECESSARY TO ENSURE THAT ENTIRE FRAME IS RIGID THROUGHOUT CONSTRUCTION. RESPONSIBILITY FOR ENSURING STABILITY OF STRUCTURE REMAINS WITH THE BUILDER.

TILT UP METHOD
FOR STRUCTURES UNDER 9M SPAN, LESS THAN 3M HIGH AND LESS THAN 12M LONG


- ASSEMBLE THE FIRST SIDEWALL FRAME (COMPLETE WITH WALL SHEETING, BRACING AND GUTTER) ON THE GROUND AND LIFT ASSEMBLED SIDEWALL FRAME INTO POSITION. FIX OFF TEMPORARY SIDE BRACING TO EACH END (REFER TO DIAGRAM). FIX BASE CLEATS.
- ASSEMBLE THE SECOND SIDEWALL FRAME AS PER FIRST SIDEWALL FRAME. LIFT INTO POSITION. FIX OFF TEMPORARY WALL BRACING TO EACH END (REFER TO DIAGRAM) FIX BASE CLEATS.
- FIX GABLE END RAFTERS TO COLUMNS TO TIE WALLS. PROP APEX UNTIL ENDWALL MULLION AND APEX TEMPORARY BRACE ARE FIXED OFF. IF NO MULLION IS REQUIRED THEN PROP AND BRACE APEX UNTIL CLADDING IS COMPLETE.
- INSTALL REMAINING RAFTERS. AS EACH RAFTER PAIR IS INSTALLED, AT LEAST ONE PURLIN PER 3M OF RAFTER LENGTH IS TO BE INSTALLED TO SECURE RAFTERS.
- INSTALL REMAINING PURLINS
- INSTALL KNEE AND APEX BRACES IF AND WHERE APPLICABLE.
- REPEAT FOR LEANTO'S.

FRAME FIRST METHOD
FOR STRUCTURES OVER 9M SPAN, GREATER THAN 3M HIGH AND GREATER THAN 12M LONG

- ASSEMBLE PORTAL FRAMES ON THE GROUND (WITH KNEE AND APEX BRACES IF AND WHERE APPLICABLE). LIFT THE FIRST PORTAL FRAME ASSEMBLY INTO POSITION. FIX OFF TEMPORARY END BRACING (REFER TO DIAGRAM). FIX BASE CLEATS.
- PROP APEX UNTIL ENDWALL MULLION AND APEX TEMPORARY BRACE ARE FIXED OFF. IF NO MULLION IS REQUIRED THEN PROP AND BRACE APEX UNTIL CLADDING IS COMPLETE.
- THE SECOND PORTAL FRAME ASSEMBLY TO BE LIFTED INTO POSITION. FIX EAVE PURLINS AND AT LEAST ONE PURLIN PER 3M OF RAFTER TO SECURE FRAME ASSEMBLY. FIX BASE CLEATS. FIX TEMPORARY SIDEWALL BRACING.
- STAND REMAINING PORTAL FRAME ASSEMBLY AS PER STEP C, FIXING TEMPORARY SIDE WALL BRACING TO EVERY SECOND BAY. BRACE OTHER END PORTAL FRAME AS PER FIRST PORTAL FRAME.
- INSTALL REMAINING PURLINS AND GIRTS.
- REPEAT FOR LEANTO'S.



1 TILT UP METHOD DIAGRAM
SCALE: NTS



2 FRAME FIRST METHOD DIAGRAM
SCALE: NTS

SHEET	7
	7
JOB NO.	LGOW/13157
DATE	30/1/2024
CHECKED	TM
DRAWN	FDB

STEEL BUILDING BY (CONTACT)
FAIR DINKUM BUILDS LITHGOW
 02 63524444
HARRISON GROSVENOR
 162 GLADSTONE STREET
 MUDGEE







NORTHERN CONSULTING engineers
 Civil & Structural Engineers
 50 Punari Street
 Currajong, Qld 4812
 Fax: 07 4725 5850
 Email: design@nceng.com.au
 ABN 341 008 173 56

Registered Chartered Professional Engineer
 Registered Professional Engineer (Civil & Structural) QLD
 Registered Certifying Engineer (Structural) N.T.
 Registered Engineer - (Civil) VIC
 Registered Engineer - (Civil) TAS

Regn. No. 2558980
 Regn. No. 9985
 Regn. No. 116373ES
 Regn. No. PE0002216
 Regn. No. CC5648M

Mr Timothy [Redacted] RPEQ
 Signature
 Date 30/1/2024
 Registered on the NPER in the areas of practice
 of Civil & Structural National Professional
 Engineers Register

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of FBHS (Aust) Pty Limited (FBHS) with whom copyright resides. The local distributor or franchisee you are dealing with is an authorised independent distributor or franchisee of FBHS' products and they enter into agreements with their customers on their own behalf and not as an agent for FBHS.



1 BOLT LAYOUT PLAN
SCALE: 1 = 100

IF YOU HAVE A ROLLER DOOR IN THE GABLE END OF YOUR SHED, CONTACT YOUR DISTRIBUTOR TO SEE IF MULLION NEEDS TO BE ROTATED FOR USE AS A DOOR JAMB.

NOT PART OF COUNCIL APPLICATION DOCUMENTATION

JOB NO. LGGW/13157	DATE 30/1/2024	CHECKED TM	DRAWN FDB
-----------------------	-------------------	---------------	--------------

STEEL BUILDING BY
FAIR DINKUM BUILDS LITHGOW
02 63524444
FOR
HARRISON GROSVENOR
AT
162 GLADSTONE STREET
MUDGEE



fair
dinkum
builds

BOLT LAYOUT PLAN

COMPLIANCE CERTIFICATE FOR BUILDING DESIGN

<p>Property Description Street address (include number, street, suburb/locality & postcode)</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">162 GLADSTONE STREET MUDGEE</td> <td style="width: 40%; text-align: right;">Postcode : 2850</td> </tr> </table>	162 GLADSTONE STREET MUDGEE	Postcode : 2850																									
162 GLADSTONE STREET MUDGEE	Postcode : 2850																											
<p>Description of Component/s Certified Clearly describe the extent of work covered by this certificate.</p>	<p>Steel Portal Frame Structure. 7m span x 12m O/A length x 3m eaves height. Consisting of 3 bays at 4m spacing.</p>																											
<p>Basis of Certification Detail the basis for giving the certificate and the extent to which tests, specifications, rules, standards, codes of practice and other publications, were relied upon.</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Australian Standards (list) AS/NZS 4600-2018, AS/NZS 1170.0,1-2002, 1170.2-2021, 1170.3-2003, 1170.4-2007, AS2870-2011, AS3600-2018, AS5216-2021</td> </tr> <tr> <td>2022 National Construction Code of Australia</td> <td>NCC Building Classification: Class 10a</td> </tr> <tr> <td>Region AS1170.2 = Reg A</td> <td>Factor for Region = NA</td> </tr> <tr> <td>NCC Importance Level = 2</td> <td>NCC Equivalent Wind class = N/A</td> </tr> <tr> <td>Annual Probability Exceedance wind = 1:500</td> <td>Design Roof Live Load = 0.25 kPa</td> </tr> <tr> <td>Regional 3 s Gust Wind Speed for annual probability of exceedance $V_R = 45$ m/s</td> <td></td> </tr> <tr> <td>Wind directional multipliers for the 8 cardinal directions $M_d = 1.00$</td> <td></td> </tr> <tr> <td>Terrain/Height multiplier (M_z, Cat) = 0.86</td> <td>Shielding Multiplier $M_s = 0.85$</td> </tr> <tr> <td>Topographic multiplier $M_t = 1$</td> <td>Design Wind Speed = 32 m/s</td> </tr> <tr> <td>Ext. Pressure Coefficient $c_{pe} = -0.65, 0.70$</td> <td>Int. Pressure Coefficient $c_{pi} = -0.58, 0.64$</td> </tr> </table>	Australian Standards (list) AS/NZS 4600-2018, AS/NZS 1170.0,1-2002, 1170.2-2021, 1170.3-2003, 1170.4-2007, AS2870-2011, AS3600-2018, AS5216-2021		2022 National Construction Code of Australia	NCC Building Classification: Class 10a	Region AS1170.2 = Reg A	Factor for Region = NA	NCC Importance Level = 2	NCC Equivalent Wind class = N/A	Annual Probability Exceedance wind = 1:500	Design Roof Live Load = 0.25 kPa	Regional 3 s Gust Wind Speed for annual probability of exceedance $V_R = 45$ m/s		Wind directional multipliers for the 8 cardinal directions $M_d = 1.00$		Terrain/Height multiplier (M_z, Cat) = 0.86	Shielding Multiplier $M_s = 0.85$	Topographic multiplier $M_t = 1$	Design Wind Speed = 32 m/s	Ext. Pressure Coefficient $c_{pe} = -0.65, 0.70$	Int. Pressure Coefficient $c_{pi} = -0.58, 0.64$							
Australian Standards (list) AS/NZS 4600-2018, AS/NZS 1170.0,1-2002, 1170.2-2021, 1170.3-2003, 1170.4-2007, AS2870-2011, AS3600-2018, AS5216-2021																												
2022 National Construction Code of Australia	NCC Building Classification: Class 10a																											
Region AS1170.2 = Reg A	Factor for Region = NA																											
NCC Importance Level = 2	NCC Equivalent Wind class = N/A																											
Annual Probability Exceedance wind = 1:500	Design Roof Live Load = 0.25 kPa																											
Regional 3 s Gust Wind Speed for annual probability of exceedance $V_R = 45$ m/s																												
Wind directional multipliers for the 8 cardinal directions $M_d = 1.00$																												
Terrain/Height multiplier (M_z, Cat) = 0.86	Shielding Multiplier $M_s = 0.85$																											
Topographic multiplier $M_t = 1$	Design Wind Speed = 32 m/s																											
Ext. Pressure Coefficient $c_{pe} = -0.65, 0.70$	Int. Pressure Coefficient $c_{pi} = -0.58, 0.64$																											
<p>Reference Documentation Clearly identify any relevant documentation, e.g numbered structural engineering plans</p>	<p>Drawing Nos: 'Fair Dinkum Builds' Structural Design Drawing To be read in conjunction with Pages 1 to 7 For Job Number: LGOW13157 DATED : 30/1/2024 Specifications: Computations: Test Reports: Other Documentation:</p>																											
<p>Competent Person Details A competent person for building work, means a person who is assessed by the building certifier for the work as competent to practise in aspect of the design, building or inspection of the building work because of the person's skill and experience in the aspect. The competent person must also be registered or licensed under a law applying in the state to practice the aspect. A COPY OF A CURRENT CV AND PROFESSIONAL REGISTRATION DETAILS MUST BE PROVIDED WITH THE CERTIFICATE</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Name:</td> <td colspan="2">Timothy Roy Messer</td> </tr> <tr> <td>Company Name (If applicable):</td> <td colspan="2">Northern Consulting Engineers</td> </tr> <tr> <td>Postal Address:</td> <td colspan="2">50 Punari Street, Currajong 4812</td> </tr> <tr> <td>Contact Person:</td> <td colspan="2">Timothy Roy Messer</td> </tr> <tr> <td>Telephone Number:</td> <td colspan="2">07 4725 5550</td> </tr> <tr> <td>Mobile Number:</td> <td colspan="2">N/A</td> </tr> <tr> <td>Fax Number:</td> <td colspan="2">07 4725 5850</td> </tr> <tr> <td>Email Address:</td> <td colspan="2">design@nceng.com.au</td> </tr> <tr> <td>License or Registration Number:</td> <td>2558980</td> <td>Copy of CV Attached: <input type="checkbox"/> Tick Box</td> </tr> </table> <div style="text-align: right; margin-top: 5px;"> <input type="checkbox"/> Y <input checked="" type="checkbox"/> or N <input checked="" type="checkbox"/> </div>	Name:	Timothy Roy Messer		Company Name (If applicable):	Northern Consulting Engineers		Postal Address:	50 Punari Street, Currajong 4812		Contact Person:	Timothy Roy Messer		Telephone Number:	07 4725 5550		Mobile Number:	N/A		Fax Number:	07 4725 5850		Email Address:	design@nceng.com.au		License or Registration Number:	2558980	Copy of CV Attached: <input type="checkbox"/> Tick Box
Name:	Timothy Roy Messer																											
Company Name (If applicable):	Northern Consulting Engineers																											
Postal Address:	50 Punari Street, Currajong 4812																											
Contact Person:	Timothy Roy Messer																											
Telephone Number:	07 4725 5550																											
Mobile Number:	N/A																											
Fax Number:	07 4725 5850																											
Email Address:	design@nceng.com.au																											
License or Registration Number:	2558980	Copy of CV Attached: <input type="checkbox"/> Tick Box																										
<p>Signature of Competent Person This form may be used by competent persons to certify the design of a material, system, method of building, building element design or other thing. If the competent person is a licensed company the authorised person of the company is to sign the form.</p>	<p>I certify that the item/s described above, if installed or carried out in accordance with the information contained in this certificate, including any referenced documentation, will comply with the National Construction Code of Australia/relevant Australian or International Standard.</p> <p>Signature of competent person: [REDACTED] Date: 30/1/2024</p>																											

LOCAL GOVERNMENT USE ONLY			
Date received		Reference Number/s	