BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1415319S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary Date of issue: Thursday, 17 August 2023 To be valid, this certificate must be lodged within 3 months of the date of issue.



Planning, Industry & Environment

Project summary				
Project name	L. Wurth			
Street address	658 Black Springs Road Budgee Budgee 2850			
Local Government Area	Mid-Western Regional Council			
Plan type and plan number	deposited 584293			
Lot no.	5			
Section no.	-			
Project type	separate dwelling house			
No. of bedrooms	4			
Project score				
Water	✓ 43 Target 30			
Thermal Comfort	V Pass Target Pass			
Energy	V 44 Target 40			

Name / Company Name: CALARE CIVIL

ABN (if applicable): 41050057933

Description of project

Project address

Project name	L. Wurth
Street address	658 Black Springs Road Budgee Budgee 2850
Local Government Area	Mid-Western Regional Council
Plan type and plan number	Deposited Plan 584293
Lot no.	5
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	4
Site details	
Site area (m²)	2000
Roof area (m ²)	166
Conditioned floor area (m2)	130.0
Unconditioned floor area (m2)	12.0
Total area of garden and lawn (m2)	200

Assessor details and thermal lo	oads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m ² .year)	n/a	
Area adjusted heating load (MJ/m ² .year)	n/a	
Ceiling fan in at least one bedroom	n/a	
Ceiling fan in at least one living room or other conditioned area	n/a	
Project score		
Water	43	Target 30
Thermal Comfort	🎺 Pass	Target Pass
Energy	V 44	Target 40

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 7.5 but <= 9 L/min) in all showers in the development.		v	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		~	
Alternative water			-
Rainwater tank			
The applicant must install a rainwater tank of at least 5000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	 Image: A set of the set of the	~
The applicant must configure the rainwater tank to collect rain runoff from at least 166 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		 	~
 the cold water tap that supplies each clothes washer in the development 		 Image: A second s	~
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	~
all hot water systems in the development		 Image: A second s	~
 all indoor cold water taps (not including taps that supply clothes washers) in the development 			

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	v	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - framed (weatherboard, fibre cement, metal clad)	2.20 (or 2.60 including construction)	
ceiling and roof - flat ceiling / pitched roof	ceiling: 4 (up), roof: foil/sarking	unventilated; medium (solar absorptance 0.475-0.70)

Note	 Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check				
Windows, glazed doors and skylights							
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~				
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~				
The following requirements must also be satisfied in relation to each window and glazed door:	~	 Image: A set of the set of the	~				
• For the following glass and frame types, the certifier check can be performed by visual inspection.			~				
- Aluminium single clear							
- Aluminium double (air) clear							
- Timber/uPVC/fibreglass single clear							
- Timber/uPVC/fibreglass double (air) clear							

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
Living	2100	2700	aluminium, single, clear	solid overhang 2400 mm, 200 mm above head of window or glazed door	not overshadowed
Entry	2100	400	aluminium, single, clear	solid overhang 2400 mm, 200 mm above head of window or glazed door	not overshadowed
Bed 1	2100	1800	aluminium, single, clear	none	not overshadowed
Bed 4	2100	1800	aluminium, single, clear	none	not overshadowed
East facing					
Bed 3	2100	1800	aluminium, single, clear	none	not overshadowed
South facing					
Kitchen	1200	1500	aluminium, single, clear	none	not overshadowed

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
Bed 2	2100	1800	aluminium, single, clear	none	not overshadowed
Laundry	2100	1800	aluminium, single, clear	none	not overshadowed
Living	2100	2100	aluminium, single, clear	none	not overshadowed
West facing					
WC	900	1200	aluminium, single, clear	none	not overshadowed
Ensuite	900	1200	aluminium, single, clear	none	not overshadowed
Bath	1500	1200	aluminium, single, clear	none	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 6 stars.	~	v	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	~
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		 	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	~
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		~	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A set of the set of the	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A set of the set of the	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		 Image: A second s	~
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
 at least 4 of the bedrooms / study; dedicated 		~	-
 at least 2 of the living / dining rooms; dedicated 		 Image: A second s	~
the kitchen; dedicated		_	~

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets; dedicated		~	~
the laundry; dedicated		~	~
all hallways; dedicated		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	 ✓ 	~	~
The applicant must install a window and/or skylight in 3 bathroom(s)/toilet(s) in the development for natural lighting.	 Image: A set of the set of the	~	~
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		_	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vi in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a vi in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a vi in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.